

INTERIM BULLETIN

Subject to Revision Without Notice

-July 15, 1971

POWER TRANSISTOR
ENGINEERING BULLETINTYPE PG1001 thru PG1017, 2 AMP NPN
SILICON PLANAR POWER TRANSISTORS

- TO-46
- 90 MHz (typical)
- 4 WATTS @ 100°C
- PREMIUM GRADE

MAXIMUM RATINGS @ 25°C AMBIENT (Unless otherwise noted.)

RATING	PG1001 PG1006 PG1012	PG1002 PG1007 PG1013	PG1003 PG1008 PG1014	2N4862 PG1009 PG1015	PG1004 PG1010 PG1016	PG1005 PG1011 PG1017	UNIT
Collector-Base Voltage	80	100	120	140	150	170	Volts
Collector-Emitter Voltage	60	80	100	120	140	160	Volts
Emitter-Base Voltage	8	8	8	8	8	8	Volts
Collector Current	2	2	2	2	2	2	Amps
Base Current	0.5	0.5	0.5	0.5	0.5	0.5	Amps
Storage Temperature			-65 to 200				°C
Operating Junction Temp.			-65 to 200				°C
Dissipation @ 100°C Case	4	4	4	4	4	4	Watts
Linear Derating Factor	40	40	40	40	40	40	mW/°C

ELECTRICAL CHARACTERISTICS @ 25°C CASE TEMPERATURE (Unless otherwise noted.)

SYMBOL	CONDITIONS	TYPES	LIMIT		UNIT
			MIN.	MAX.	
I_{CEX}	$V_{CE} = 60V, V_{BE} = -0.5V, T_C = 150^\circ C$	All		10	μA
I_{CEX}	$V_{CE} = \text{MAX RATING}, V_{BE} = -0.5V$	All		10	μA
I_{CBO}	$V_{CB} = 60V, I_E = 0$	All		0.1	μA
I_{EBO}	$V_{EB} = 8V$	All		10	μA
$BV_{CEO(sus)}^*$	$I_B = 0, I_C = 10mA$	All	Max. Rating		Volts
I_{CEO}	$I_B = 0, V_{CE} = 60V$	All		10	μA
h_{FE}^*	$I_C = 2A, V_{CE} = 5V$	PG1001 thru PG1005	15		

PIRGO ELECTRONICS INC.

A Sprague Electric Company Subsidiary

Pembroke Road, Concord, N.H. 03301

PG--1001-1X

TYPE P 1001 thru P 1017, 2 AMP NPN
SILICON PLANAR POWER TRANSISTORSENGINEERING
BULLETIN
31, 513

ELECTRICAL CHARACTERISTICS @ 25°C (Continued)

SYMBOL	CONDITIONS	TYPES	LIMIT		UNIT
			MIN.	MAX.	
h_{FE}^*	$I_C = 2A, V_{CE} = 5V$	PG1006	10		
		thru			
		PG1011			
		PG1012	20		
	$I_C = 0.5A, V_{CE} = 5V$	thru			
		PG1017			
		PG1001	50	150	
		thru			
		PG1005			
		PG1006	30	90	
$V_{CE(sat)}^*$	$I_C = 2A, I_B = 0.2A$	thru			
		PG1011			
		PG1012	100	300	
V_{BE}^*	$I_C = 0.5A, V_{CE} = 5V$	thru			
		PG1017			
		All		1.5	Volts
$ h_{fe} $	$V_{CE} = 10V, I_C = 0.1A, f = 10MHz$	All		0.2	Volts
		All		1.2	Volts
h_{fe}	$V_{CE} = 5V, I_C = 50mA, f = 1 KHz$	All	5		
		PG1001	50		
		thru			
		PG1005			
		PG1006	30		
		thru			
C_{ob}	$V_{CB} = 10V, I_C = 0, f = 1 MHz$	PG1011			
		PG1012	70		
		thru			
		PG1017			
		All		50	pf

*Pulsed measurement: $PW \leq 330\mu sec$; $\leq 2\%$ duty cycle.

Information furnished by PIRGO is believed to be accurate and reliable. However, no responsibility is assumed by PIRGO for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of PIRGO.

Litho in U.S. Amer.

PG--1001-2X